

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: GC Fuji LINING LC Paste Pak Paste B · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Auxillary for dental technology • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax + 32/(0)16/40.26.84msds@gc.dental · Further information obtainable from: Regulatory affairs · 1.4 Emergency telephone number: National poison center for United Kingdom of Great Britain and Northern Ireland: Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383 Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180 Penarth: +44 292 071 55 54 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Exemptions The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5). · Hazard pictograms



*

· Signal word Danger

(Contd. on page 2)

[—] GB

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

	(Contd. of page 1)
· Hazard-determini	ng components of labelling:
2-hydroxyethyl me	
Tartaric acid	·
· Hazard statements	
H315 Causes skin	irritation.
H318 Causes serio	us eye damage.
H317 May cause a	n allergic skin reaction.
H412 Harmful to a	equatic life with long lasting effects.
· Precautionary stat	ements
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P305+P351+P338	B IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
· 2.3 Other hazards	
· Results of PBT an	d vPvB assessment
• PBT: Not applicab	
• vPvB: Not applica	ble.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

• Dangerous components:		
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl metacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-<50%
CAS: 9003-01-4	Polyacrylic acid Eye Irrit. 2, H319	25-<50%
CAS: 1830-78-0 EINECS: 217-388-4	2-Hydroxy-1,3 dimethacryloxypropane Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 87-69-4 EINECS: 201-766-0	Tartaric acid Eye Dam. 1, H318	5-<10%
CAS: 7631-86-9 EINECS: 231-545-4	silicon dioxide Nanoform: Spheroidal, amorphous nanoform, set including amorphous nanoforms, amorphous forms, non-surface- treated nanoforms	1-<2.5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-<0.5%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

(Contd. on page 3)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

- If symptoms persist consult doctor. • After inhalation:
- Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. Seek medical treatment. If skin irritation continues, consult a doctor.
 After eye contact:
- Protect unharmed eye. Rinse opened eye for several minutes under running water. If symptoms persist consult doctor. Call a doctor immediately.
- · After swallowing:
- Rinse out mouth and then drink plenty of water.
- If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Remove persons from danger area. Avoid contact with the eyes and skin. Wear protective clothing.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Do not allow to penetrate the ground/soil.
6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material. Dispose of the material collected according to regulations.

(Contd. on page 4)

GB

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

(Contd. of page 3)

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with the eyes and skin.

· Information about fire - and explosion protection: Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

128-37-0 Butylated hydroxytoluene

Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m3 (man)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

(Contd. of page 4)

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical prope	rties
· General Information	
· Physical state	Fluid
· Colour:	Yellow
· Odour:	Characteristic
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Ignition temperature:	Undetermined.
· Decomposition temperature:	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Particle characteristics	Diameter particle structure = $2.5 - 50$ nm (TEM, $d50$, number-based)
	Diameter $agglomerate = 5 - 50 mm$ (laser diffraction dry module, $d50$, volume based)
	7631-86-9 silicon dioxide: Spheroidal, amorphous
	nanoform, set including amorphous nanoforms, amorphous forms, non-surface-treated nanoforms
9.2 Other information	
· Appearance:	D
· Form:	Pasty

(Contd. on page 6)

GB

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

	(Contd. of pag
Important information on protection of hea	ilth and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
Water:	26.8 %
VOC (EC)	0.0 g/l
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cla	isses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammab	ble gases
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity
- · LD/LC50 values relevant for classification:
- 7631-86-9 silicon dioxide

Oral LD50 10,000 mg/kg (rat (f+m))

128-37-0 Butylated hydroxytoluene

Oral LD50 >6,000 mg/kg (rat (f+m)) (OECD 401)

(Contd. on page 7)

GB -

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

(Contd. of page 6)

List II

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

• Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

· Additional toxicological information:

- *Repeated dose toxicity No further relevant information available.*
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

• 11.2 Information on other hazards

· Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*
- *Recommended cleansing agents: Water, if necessary together with cleansing agents.*

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA

not regulated

(Contd. on page 8)

βB

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

		(Contd. of page 7
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	not regulated	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	not regulated	
· 14.4 Packing group · ADR, IMDG, IATA	not regulated	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	
· UN "Model Regulation":	not regulated	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. · Classification according to Regulation (EC) No 1272/2008 Calculation method · Department issuing SDS: Regulatory affairs · Contact: msds@gc.dental · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_B

	of page 8)
vPvB: very Persistent and very Bioaccumulative	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Skin Sens. 1: Skin sensitisation – Category 1	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 1. Indiardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
Sources	
• ECHA (http://echa.europa.eu/)	
• EnviChem (www.echemportal.org)	
* Data compared to the previous version altered.	
This version replaces all previous versions.	
Disclaimer:	
The information contained herein is believed to be true and accurate. However, all statements, recommen or suggestions are made without any guarantee, representation or warranty, express or implied, on or	ur part.
Therefore, no warranty is made or to be implied that the information set out in this document is accur complete, and we accordingly exclude all liability in connection with the use of this information or the p referred to herein. All such risks are assumed by the purchaser/user. The information contained herein which to change without acting. For the model of doubt how much nothing in this document and	products 1 is also
subject to change without notice. For the avoidance of doubt, however, nothing in this document excl limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation	



Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: GC Fuji LINING LC Paste Pak Paste A · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Auxillary for dental technology • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax + 32/(0)16/40.26.84msds@gc.dental · Further information obtainable from: Regulatory affairs · 1.4 Emergency telephone number: National poison center for United Kingdom of Great Britain and Northern Ireland: Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383 Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180 Penarth: +44 292 071 55 54 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Exemptions The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from

labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms



*

· Signal word Warning

(Contd. on page 2)

⁻ GB

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

	(Contd. of page 1)
· Hazard-determ	ining components of labelling:
2-hydroxyethyl	
Urethane Dime	thacrylate (UDMA)
Hazard statem	ents
H315 Causes s	kin irritation.
H319 Causes s	erious eye irritation.
H317 May cau	se an allergic skin reaction.
H412 Harmful	to aquatic life with long lasting effects.
Precautionary	statements
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection / face protection.
P305+P351+P	<i>P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
2.3 Other haza	rds
· Results of PBT	and vPvB assessment
• PBT: Not appl	icable.
	1. 11

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

 Dangerous components: 		
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X	2-hydroxyethyl metacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<25%
CAS: 1830-78-0 EINECS: 217-388-4	2-Hydroxy-1,3 dimethacryloxypropane Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 72869-86-4 EINECS: 276-957-5	Urethane Dimethacrylate (UDMA) Aquatic Chronic 2, H411; Skin Sens. 1B, H317	5-<10%
CAS: 68909-20-6 EINECS: 272-697-1	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica Nanoform: Spheroidal, amorphous nanoform, set including amorphous nanoforms, amorphous forms, surface-treated nanoforms	
CAS: 1879-09-0 EINECS: 217-533-1	6-tert-butyl-2,4-xylenol Acute Tox. 2, H310; STOT RE 2, H373; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-<0.2%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	1

(Contd. on page 3)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

- If symptoms persist consult doctor.
- *After inhalation:* Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
- Take affected persons into fresh air and keep quiet.
- After skin contact:

Immediately wash with water and soap and rinse thoroughly. Seek medical treatment.

If skin irritation continues, consult a doctor.

After eye contact: Protect unharmed eye. Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing:
- Rinse out mouth and then drink plenty of water.
- If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Remove persons from danger area. Avoid contact with the eyes and skin. Wear protective clothing.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to penetrate the ground/soil. In case of seepage into the ground inform responsible authorities.
6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material. Dispose of the material collected according to regulations.

(Contd. on page 4)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

(Contd. of page 3)

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

· 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with the eyes and skin.

· Information about fire - and explosion protection: Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.

· Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions: None.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

1879-09-0 6-tert-butyl-2,4-xylenol

Inhalative DNEL inhalation 0.14 mg/m3 (man)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- *Respiratory protection:* Suitable respiratory protective device recommended.
- · Hand protection



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

General Information	
Physical state	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling ran	ge Undetermined.
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
· Upper:	Not determined.
Flash point:	97 °C
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Insoluble.
Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
Density and/or relative density	
Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
Particle characteristics	Diameter particle structure = $2.5 - 50$ nm (TEM, $d50$ number-based)
	Diameter $agglomerate = 5 - 50 mm$ (laser diffraction dry module, d50, volume based)
	68909-20-6 Silanamine, 1,1,1-trimethyl-N
	(trimethylsilyl)-, hydrolysis products with silica
	Spheroidal, amorphous nanoform, set including
	amorphous nanoforms, amorphous forms, surface treated nanoforms
	(Contd. on page

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

	(Contd. of page
9.2 Other information	
Appearance:	
Form:	Pasty
Important information on protection of hea	alth and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Solvent content:	
VOC (EC)	0.0 g/l
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cla	isses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammal	ble gases
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity

· LD/LC50 values relevant for classification:

72869-86-4 Urethane Dimethacrylate (UDMA)

Oral | LD50 | >5,000 mg/kg (rat female) (OECD 401)

(Contd. on page 7)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

(Contd. of page 6)

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

1879-09-0 6-tert-butyl-2,4-xylenol

Oral LD50 910 mg/kg (rat (f+m)) (OECD 401)

Dermal LD50 <200 mg/kg (rabbit) (OECD 402)

Skin corrosion/irritation Causes skin irritation.

• Serious eye damage/irritation Causes serious eye irritation.

• Respiratory or skin sensitisation May cause an allergic skin reaction.

• Additional toxicological information:

• *Repeated dose toxicity No further relevant information available.*

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- No further relevant information available.

• 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

(Contd. on page 8)

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

(Contd. of page 7)

14.1 UN number or ID number		
ADR, ADN, IMDG, IATA	not regulated	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	not regulated	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	not regulated	
14.4 Packing group		
ADR, IMDĞ, IATA	not regulated	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	not regulated	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

· Relevant phrases

H302 Harmful if swallowed.

- H310 Fatal in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2022

Version number 3 (replaces version 2)

Revision: 15.12.2022

Trade name: GC_Fuji_LINING_LC_Paste_Pak_Paste_A

(Contd. of page 8) CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 Sources • ECHA (http://echa.europa.eu/) • EnviChem (www.echemportal.org) • * Data compared to the previous version altered. This version replaces all previous versions. Disclaimer: The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.