Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Start

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Prime & Bond NT

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the mixture Adhesive
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Dentsply DeTrey GmbH De-Trey-Str. 1 D-78467 Konstanz GERMANY Tel.: +49-(0)7531-583-0 Fax: +49-(0)7531-583-104 email: KonstanzDEU.info-sdb@dentsplysirona.com

- Further information obtainable from: Research and Development
- 1.4 Emergency telephone number: +49-(0)7531-583-0 8:00 17:00 (GMT + 1:00)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

- · Classification according to Regulation (EC) No 1272/2008
- *Flam. Liq. 2 H225 Highly flammable liquid and vapour.*
- Skin Irrit. 2 H315 Causes skin irritation.
- *Eye Irrit.* 2 *H319 Causes serious eye irritation.*
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- *Repr. 1B* H360 May damage fertility or the unborn child.
- STOT SE 3 H336 May cause drowsiness or dizziness.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- Additional information:

The reproductive toxicity effect only occurs when several bottles of Prime & Bond NT are used daily on a 50 kg patient.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling: acetone
Di(ethylene glycol) dimethacrylate
Ethyl-4-dimethylaminobenzoat
Hazard statements
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

		(Contd. of page 1)
•	Precautionary state	ments
		Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
		IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
		<i>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
	P405	Store locked up.
		<i>Dispose of contents/container in accordance with local/regional/national/international regulations.</i>
•	Additional informa	tion:
	As this product is a	medical device in the meaning of Directive 93/42/EEC and regulation (EC) 2017/745 and the and consumer and is applied in an imagine meaner or body contact, it is grown the

intended for use by the end consumer and is applied in an invasive manner or body contact, it is exempt from the labelling requirements according to regulation (EC) 1272/2008.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	50-100%
CAS: 105883-40-7	Urethane Dimethacrylate Resin Skin Irrit. 2, H315; Eye Irrit. 2, H319	10-25%
CAS: 87699-25-0	Dipentaerythritol pentaacrylate phosphate Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Specific concentration limit: STOT SE 3; $C \ge 10 \%$	≥ 2.5 - < 10%
CAS: 2358-84-1	Di(ethylene glycol) dimethacrylate Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5 - 10%
CAS: 68909-20-6 EINECS: 272-697-1	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products withsilica STOT RE 2, H373, EUH066	≥ 2.5 - < 10%
CAS: 3290-92-4	propylidynetrimethyl trimethacrylate Aquatic Chronic 2, H411	≥ 0.25 - < 2.5%
CAS: 10287-53-3	<i>Ethyl-4-dimethylaminobenzoat</i> <i>Repr. 1B, H360; Aquatic Chronic 2, H411</i>	≥ 0.3 - < 2.5%
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119565113-46-XX	2,6-di-tert-butyl-p-cresol Aquatic Acute 1, H400; Aquatic Chronic 1, H410 XX	≥ 0.25 - < 2.5%
<u> </u>	wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · *General information Immediately remove any clothing soiled by the product.*
- · After inhalation Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

(Contd. of page 2)

Trade name: Prime & Bond NT

- After skin contact Immediately wash with water and soap and rinse thoroughly.
- · After eye contact
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing If symptoms persist consult doctor.
- · Information for doctor No further relevant information available.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
Observe normal care for working with chemicals.
Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges. Keep respiratory protective device available.

- · Handling Product is intended for dental use only.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- *Requirements to be met by storerooms and receptacles: Store in a cool location.*

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

Store only in the original receptacle.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

• **Regulatory information** WEL: EH40/2020

· DNELs

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

Inhalative Long-term - systemic effects, worker 3.5 mg/m3 (rat)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

• Hand protection



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Natural rubber, NR

Recommended thickness of the material: ≥ 0.75 mm

Permeation: Level ≥ 2

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles.

(Contd. on page 5)

(Contd. of page 3)

Printing date 24.04.2023

Version number 9 (replaces version 8)

Trade name: Prime & Bond NT

*

• *Body protection: Protective work clothing.*

SECTION 9: Physical and chemical prop	erties
9.1 Information on basic physical and chemical p	roperties
General Information	
Physical state	Fluid
Colour:	Yellow
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	undetermined
Boiling point or initial boiling point and boiling	
range	≥ 56 °C (CAS: 67-64-1 acetone)
Flammability	Highly flammable.
Lower and upper explosion limit	ingniy jummuole.
Lower:	2.6 Vol %
Upper:	12.8 Vol %
Flash point:	-19 °C (c.c. Abel)
Auto-ignition temperature:	527.5 °C (CAS: 67-64-1 acetone)
	Not applicable
Decomposition topps quatures.	Not determined.
Decomposition temperature:	Not determined.
pH Viacositu	ivoi ueierminea.
Viscosity:	Not determined
Kinematic viscosity	Not determined.
dynamic:	Not determined.
Solubility	B
Water:	Partly miscible
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	233 hPa
Density and/or relative density	
Density at 20 °C:	$0.9 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and	d
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
1 <u>r</u> . <u>r</u>	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	67.0 %
Solids content:	3.0%
Change in condition	
Evaporation rate	Not determined.
*	
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void

(Contd. on page 6)

Revision: 24.04.2023

(Contd. of page 4)

GB

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

		(Contd. of page 5)
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamme	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

CAS: 67-6			
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	76 mg/l (rat)	
CAS: 3290)-92-4 proj	ylidynetrimethyl trimethacrylate	
Oral	LD50	> 2,000 mg/kg (rat)	
CAS: 1028	87-53-3 Et	hyl-4-dimethylaminobenzoat	
Oral	LD50	> 2,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	> 2,000 mg/kg (rat)	
CAS: 128-	37-0 2,6-d	i-tert-butyl-p-cresol	
Oral	LD50	2,930 mg/kg (rat)	
Dermal	LD50	> 2,000 mg/kg (rat)	
		tion Causes skin irritation.	
		irritation Causes serious eye irritation. ensitisation May cause an allergic skin reaction.	
		May damage fertility or the unborn child.	
		re May cause drowsiness or dizziness.	
11.2 Infor	mation on	other hazards	
Endocrine	disrupting	g properties	
CAS: 128-	37-0 2,6-a	li-tert-butyl-p-cresol	List 1
Other info	rmation		I

(Contd. on page 7)

GR

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

• Aquatic toxicity: CAS: 67-64-1 acetone

LC50/96h 5,540 mg/l (Fish acute toxicity study)

EC50/48h 6,100 mg/L (daphnia magna)

CAS: 3290-92-4 propylidynetrimethyl trimethacrylate

LC50/96h 2 mg/l (Fish acute toxicity study)

EC50/48h > 9.22 mg/L (daphnia magna)

CAS: 128-37-0 2,6-di-tert-butyl-p-cresol

LC50/48h 0.199 mg/l (Fish acute toxicity study)

EC50/48h 0.758 mg/L (Alg)

0.48 mg/L (daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*
- *Recommended cleansing agents: Water, if necessary together with cleansing agents.*

SECTION 14: Transport information		
· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1090	
· 14.2 UN proper shipping name		
·ADR	1090 ACETONE mixture	
· IMDG, IATA	ACETONE mixture	
		(Contd. on page 8

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

	(Contd. of pag
· 14.3 Transport hazard class(es)	
· ADR	
3	
•	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
V	
· Class	3 Flammable liquids.
·Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	E
· 14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
—	Maximum net quantity per outer packaging: 500 ml
• Transport category	2 D/F
• Tunnel restriction code	D/E
·IMDG	
Limited quantities (LQ)	
· Excepted quantities (EQ)	Code: E2 Manimum not quantity non-inner na chaoing: 20 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1090 ACETONE MIXTURE, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

(Contd. on page 9)

GB

Printing date 24.04.2023

Version number 9 (replaces version 8)

Revision: 24.04.2023

Trade name: Prime & Bond NT

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The attached safety data sheet covers the dangers and measures to be taken when large quantities of material are released, for example due to accidents during transport or storage by the dealer. For quantities of material typically used in clinical practice, information necessary for safe use and storage of the product is given in the DFU.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Research & Development

• Contact: HotLine for urgent technical support: +49-7531-583-350

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1B: Reproductive toxicity - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• * Data compared to the previous version altered.